

Landgrebe Manufacturing, Inc.

TD 40 – Cycle Tow Dolly Model 48



Specifications – Will tow a motorcycle or golf-cart

Total Unit Weight: 800 lbs platform size 48"x96"	Tongue Weight: 315 lbs (add more if you add rock deflector or spare tire)
Loading ramp 43 lbs	Loading ramp length 60"
Loading ramp angle 16 degrees	Loading ramp width 18"
Total Length Electric Brakes 170"	Total Length Hydraulic Brakes 172"
Cycle Transport Rail width 40" inside diam.	Cycle Transport Rail Length 96"
Front Tire Bail For Cycle 7" wide-folds down for drive thru	205 75 R15 LRC Tires: 1820 lbs Capacity Each 50 lbs Air
Total Load Capacity: 3500 lbs Spindle Capacity	Electric & Hydraulic Brakes rated at 7500 pulling
Deck Platform off ground approx. 17"	Dolly overall width 103"
Dolly Inside Fender 85"	Dolly In Between Ramps 40"
Dolly ramp width each 19"	Dolly outside ramp 78"
10"x2" 1/4 Drum type brakes elec or hyd	Wired w/4 way flat w/hyd brakes 7 way Bargeman w/elec brakes
6 bolt 5/12" Bolt Circle 1/2" offset mod wheels 3 1/4 pilot	Ramp loading angle tilted approximately 14 degrees
Caster Action Steering with stabilizer tie rod with Heim Bearings	All wiring and plumbing run inside Frame double insulated
Main Frame and Tongue 2x2x4/16 tubing	Safety Cable for Towed Vehicle
4 way flat provided at rear of drivers side of fender for towed vehicle	Ground to Top of Fender: 28"
Safety chains 5/16 proof coil 30 plus	Approximate dimension center-line of towed vehicle axle to ball: 140"
Ramp height 9" Ramp to top of Fender: 19"	Optional Aluminum Deck Platform
Optional PVC Rock Guard 8"x24" high-- optional spare tire & wheel	Optional Aluminum Rock Guard