

# Landgrebe Manufacturing, Inc.

## TD 40 96 – Model



### Specifications – Will Tow a Vehicle up to 72"

Total Unit Weight: 468	Tongue Weight: 53 lbs
Spare Tire and Wheel : Add 40 lbs.	Electric Brakes: 40 lbs
Total Length: Hydraulic Brakes: 123"	Total Length: Electric Brakes: 123"
Electric Brakes Overall Width: 100"	Inside Fender: 81"
Outside Ramps: 75"	Distance Between Ramps: 43"
Ramp Width Each: 16"	205 75 R14 LRC Tires: 1820 lbs Capacity Each 50 lbs Air
Total Load Capacity: 3500 lbs Spindle Capacity	Tow Capacity: Electric: 5000 lbs
Tow Capacity: Hydraulic Surge: 6000 lbs	10"x2 ¼" Drum type Brakes Electric or Hydraulic
Electric Brake-Away Kit Optional	Wired with 4 way flat with Hydraulic Brakes
7 way Bargeman with Electric Brakes	2 " Ball required for both brake systems
19 " top of Ball Hydraulic	18 ½" top of Ball w/elec Brakes
5 bolt 4½" Bolt Circle	½ " offset mod wheels 3 ¼ pilot
Caster Action Steering with stabilizer tie rod with Heim Bearings	Ramp loading angle tilted approximately 14 degrees
Main Frame and Tongue 2x2x3/16 tubing	All wiring and plumbing run inside Frame double insulated
4 way flat provided at rear of drivers side of fender for towed vehicle	Paint colors on request
Safety chains 5/16 proof coil 30 plus	Safety Cable for Towed Vehicle
Ramp height 9"	Ramp to top of Fender: 19"
Ground to Top of Fender: 28"	Approximate dimension center-line of towed vehicle axle to ball elec-79" Hyd 83"