

Landgrebe Manufacturing, Inc.

TD 40 – Cycle Tow Dolly Model 24



Specifications – Will tow a scooter & small bike

Total Unit Weight: 925 lbs. w/platform 24"x80"	Tongue Weight: approx. 250 lbs. (add more if you add rock deflector or spare tire)
Loading ramp 43 lbs.	Loading ramp length 5'
Loading ramp angle 16 degrees	Loading ramp width 24"
Total Length Electric Brakes 128"	Total Length Hydraulic Brakes 135"
Cycle Transport Rail width 24" inside diam.	Cycle Transport Rail Length 96"
Front Tire Bail For Cycle 7" wide-folds down for drive thru	205 75 R15 LRC Tires: 1820 lbs. Capacity Each 50 lbs Air
Total Load Capacity: 3500 lbs Spindle Capacity	Electric & Hydraulic Brakes rated at 7500 pulling
Deck Platform off ground approx. 17"	Dolly overall width 103"
Dolly Inside Fender 85"	Dolly In Between Ramps 40"
Dolly ramp width each 19"	Dolly outside ramp 78"
10"x2" ¼ Drum type brakes elec or hyd	Wired w/4 way flat w/hyd brakes 7 way Bargeman w/elec brakes
6 bolt 5½" Bolt Circle ½ " offset mod wheels 3 ¼ pilot	Paint codes available on request
Caster Action Steering with stabilizer tie rod with Heim Bearings	Ramp loading angle tilted approximately 14 degrees
Main Frame and Tongue 2x2x3/16 tubing	All wiring and plumbing run inside Frame double insulated
4 way flat provided at rear of drivers side of fender for towed vehicle	Paint Codes: Body 325N119 Dark Smoke, Tongue 325N121 Lt Smoke, Industrial Primer Sealer and Acrylic Enamel with clear coat on top
Safety chains 5/16 proof coil 30 plus	Safety Cable for Towed Vehicle
Ramp height 9" Ramp to top of Fender: 19"	Ground to Top of Fender: 28"
PVC Rock Guard 8"x24" high-- optional spare tire & wheel	Approximate dimension center-line of towed vehicle axle to ball: 116"